

# DIESEL GENERATOR SET



## DE33E0 (LC Frame)

Image shown may not reflect actual package

Output Ratings		
Generator Set Model - 3 Phase	Prime*	Standby*
400/230 V, 50 Hz	30.0 kVA 24.0 kW	33.0 kVA 26.4 kW
480V, 60 Hz	33.8 kVA 27.0 kW	37.5 kVA 30.0 kW

\* Refer to ratings definitions on page 4.  
Ratings at 0.8 power factor.

Technical Data		
Engine Make & Model:	Cat® C3.3	
Generator Model:	LC1514F	
Control Panel:	EMCP 4.1	
Base Frame Type:	Heavy Duty Fabricated Steel	
Circuit Breaker Type:	3 Pole MCB / 3 Pole MCCB	
Frequency:	50 Hz	60 Hz
Engine Speed: RPM	1500	1800
Fuel Tank Capacity: litres (US gal)	161 (42.5)	
Fuel Consumption, Prime: l/hr (US gal/hr)	7.0 (1.8)	8.1 (2.1)
Fuel Consumption, Standby : l/hr (US gal/hr)	7.7 (2.0)	9.0 (2.4)

# DIESEL GENERATOR SET



## Engine Technical Data

Physical Data	
<b>Manufacturer:</b>	Caterpillar
<b>Model:</b>	C3.3
<b>No. of Cylinders/Alignment:</b>	3 / In Line
<b>Cycle:</b>	4 Stroke
<b>Induction:</b>	Naturally Aspirated
<b>Cooling Method:</b>	Water
<b>Governing Type:</b>	Mechanical
<b>Governing Class:</b>	ISO 8528 G2
<b>Compression Ratio:</b>	19.25:1
<b>Displacement: l (cu.in)</b>	3.3 (201.4)
<b>Bore/Stroke: mm (in)</b>	105.0 (4.1)/127.0 (5.0)
<b>Moment of Inertia: kg m<sup>2</sup> (lb. in<sup>2</sup>)</b>	1.14 (3896)
<b>Engine Electrical System:</b>	
-Voltage/Ground:	12/Negative
-Battery Charger Amps:	65
<b>Weight: kg (lb) - Dry:</b>	412 (908)
- Wet:	430 (948)

Air System		50 Hz	60 Hz
<b>Air Filter Type:</b>		Replaceable Element	
<b>Combustion Air Flow:</b>			
m <sup>3</sup> /min (cfm)	<b>-Standby:</b>	2.2 (76)	2.6 (91)
	<b>-Prime:</b>	2.2 (76)	2.6 (92)
<b>Max. Combustion Air Intake</b>			
<b>Restriction: kPa (in H<sub>2</sub>O)</b>		6.5 (26.1)	6.5 (26.1)
<b>Radiator Cooling Air Flow:</b>			
m <sup>3</sup> /min (cfm)		62.6 (2211)	84.8 (2995)
<b>External Restriction to</b>			
<b>Cooling Air Flow: Pa (in H<sub>2</sub>O)</b>		125 (0.5)	125 (0.5)

Cooling System		50 Hz	60 Hz
<b>Cooling System Capacity:</b>			
l (US gal)		10.2 (2.7)	10.2 (2.7)
<b>Water Pump Type:</b>		Centrifugal	
<b>Heat Rejected to Water &amp; Lube Oil: kW (Btu/min)</b>			
	<b>-Standby:</b>	18.0 (1024)	22.0 (1251)
	<b>-Prime:</b>	16.0 (910)	18.0 (1024)
<b>Heat Radiation to Room: Heat radiated from engine and alternator</b>			
kW (Btu/min)	<b>-Standby:</b>	9.3 (529)	9.7 (552)
	<b>-Prime:</b>	7.9 (449)	8.2 (466)
<b>Radiator Fan Load: kW (hp)</b>		0.3 (0.4)	0.5 (0.7)
Cooling system designed to operate in ambient conditions up to 50°C (122°F). Contact your local Cat dealer for power ratings at specific site conditions.			

Lubrication System	
<b>Oil Filter Type:</b>	Spin-On, Full Flow
<b>Total Oil Capacity l (US gal):</b>	8.3 (2.2)
<b>Oil Pan l (US gal):</b>	7.8 (2.1)
<b>Oil Type:</b>	API CG4 / CH4 15W-40
<b>Cooling Method:</b>	Water

Performance	50 Hz	60 Hz
<b>Engine Speed: RPM</b>	1500	1800
<b>Gross Engine Power: kW (hp)</b>		
-Standby:	31.0 (42.0)	36.5 (49.0)
-Prime:	28.2 (38.0)	33.1 (44.0)
<b>BMEP: kPa (psi)</b>		
-Standby:	752.0 (109.0)	738.0 (107.0)
-Prime:	684.0 (99.2)	669.0 (97.0)
<b>Regenerative Power: kW</b>	7.0	9.0

Fuel System				
<b>Fuel Filter Type:</b>	Replaceable Element			
<b>Recommended Fuel:</b>	Class A2 Diesel or BSEN590			
<b>Fuel Consumption: l/hr (US gal/hr)</b>				
	<b>110% Load</b>	<b>100% Load</b>	<b>75% Load</b>	<b>50% Load</b>
<b>Prime</b>				
50 Hz	7.7 (2.0)	7.0 (1.8)	5.2 (1.4)	3.8 (1.0)
60 Hz	9.0 (2.4)	8.1 (2.1)	6.2 (1.6)	4.7 (1.2)
<b>Standby</b>				
50 Hz		7.7 (2.0)	5.7 (1.5)	4.1 (1.1)
60 Hz		9.0 (2.4)	6.8 (1.8)	5.0 (1.3)
(based on diesel fuel with a specific gravity of 0.85 and conforming to BS2869, Class A2)				

Exhaust System		50 Hz	60 Hz
<b>Silencer Type:</b>		Industrial	
<b>Silencer Model &amp; Quantity:</b>		EXSY1 (1)	
<b>Pressure Drop Across</b>			
<b>Silencer System: kPa (in Hg)</b>		1.80 (0.532)	2.00 (0.591)
<b>Silencer Noise Reduction</b>			
<b>Level: dB</b>		20	19
<b>Max. Allowable Back</b>			
<b>Pressure: kPa (in. Hg)</b>		8.0 (2.4)	10.0 (3.0)
<b>Exhaust Gas Flow:</b>			
m <sup>3</sup> /min (cfm)	<b>-Standby:</b>	5.8 (205)	6.6 (233)
	<b>-Prime:</b>	5.7 (201)	6.4 (226)
<b>Exhaust Gas Temperature: °C (°F)</b>			
	<b>-Standby:</b>	520 (968)	530 (986)
	<b>-Prime:</b>	500 (932)	520 (968)

# DIESEL GENERATOR SET



## Generator Performance Data

Data Item	50 Hz				60 Hz				
	415/240V	400/230V 230/115V 200/115V	380/220V 220/110V	220/127V	480/277V 240/139V	380/220V 220/110V	240/120V 208/120V		440/254V 220/127V
Motor Starting Capability* kVA	72	68	63	78	78	55	63		69
Short Circuit Capacity %	-	-	-	-	-	-	-		-
Reactances: Per Unit									
Xd	2.298	2.474	2.741	2.045	2.323	3.706	3.092		2.764
X'd	0.143	0.153	0.170	0.127	0.144	0.230	0.192		0.171
X''d	0.071	0.077	0.085	0.063	0.072	0.115	0.096		0.086

Reactances shown are applicable to prime ratings.  
\*Based on 30% voltage dip at 0.6 power factor.

## Generator Technical Data

Physical Data	
LC Frame	
Model:	LC1514F
No. of Bearings:	1
Insulation Class:	H
Winding Pitch - Code:	2/3 - 6
Wires:	12
Ingress Protection Rating:	IP23
Excitation System:	SHUNT
AVR Model:	R220

Operating Data	
Overspeed: RPM	2250
Voltage Regulation: (steady state)	+/- 1.0%
Wave Form NEMA = TIF:	50
Wave Form IEC = THF:	2.0%
Total Harmonic Content LL/LN:	5.0%
Radio Interference:	Suppression is in line with European Standard EN61000-6
Radiant Heat: kW (Btu/min)	
-50 Hz:	3.3 (188)
-60 Hz:	3.7 (210)

# DIESEL GENERATOR SET



## Technical Data


Voltage 50 Hz	Prime		Standby	
	kVA	kW	kVA	kW
415/240V	30.0	24.0	33.0	26.4
400/230V	30.0	24.0	33.0	26.4
380/220V	30.0	24.0	33.0	26.4
230/115V	30.0	24.0	33.0	26.4
220/127V	30.0	24.0	33.0	26.4
220/110V	30.0	24.0	33.0	26.4
200/115V	30.0	24.0	33.0	26.4

Voltage 60 Hz	Prime		Standby	
	kVA	kW	kVA	kW
480/277V	33.8	27.0	37.5	30.0
220/127V	33.8	27.0	37.5	30.0
380/220V	33.8	27.0	37.5	30.0
240/120V	33.8	27.0	37.5	30.0
220/110V	33.8	27.0	37.5	30.0
208/120V	33.8	27.0	37.5	30.0
240/139V	33.8	27.0	37.5	30.0

## Weights & Dimensions

Weights: kg (lb)	
Net (+ lube oil)	827 (1823)
Wet (+ lube oil & coolant)	840 (1852)
Fuel, lube oil & coolant	976 (2153)

Dimensions: mm (in)	
Length	1540 (60.6)
Width	970 (38.2)
Height	1361 (53.6)



**Note:** General configuration not to be used for installation. See general dimension drawings for detail.

## Definitions

### Standby Rating

Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year.

### Prime Rating

Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand is 100% of prime rated kW with 10% overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year.

### Standard Reference Conditions

Note: Standard reference conditions 25°C (77°F) air inlet temp, 100m (328ft) A.S.L. 30% relative humidity. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.

## General Data

### Documents

A full set of operation and maintenance manuals and circuit wiring diagrams.

### Quality Standards

The equipment meets the following standards: **IEC60034-1, IEC60034-22, ISO3046, ISO8528, NEMA MG 1-32, NEMA MG 1-33, 2004/108/EC, 2006/42/EC, 2006/95/EC.**